



ATF LoVis & HiVis 100% SYNTHETIC AUTOMOTIVE TRANSMISSION FLUID

DESCRIPTION:

Torco 100% synthetic ATF is formulated using premium synthetic base oils and our advanced additive technology to provide smooth operation with superior wear protection and oxidation stability when pushing your vehicle to the limit in racing, high-performance street, or off-road driving. This combination of premium synthetic base oils and advanced additive technology can withstand intense heat and shearing forces to protect your transmission from the damaging effects of sludge, varnish, and wear.

FEATURES & BENEFITS:

- Premium shear-stable synthetic base oils and advanced additive technology help prevent viscosity loss
- Exceptional thermal and oxidation stability significantly reduces operating temperatures
- Superior wear protection extends the life of clutches, bearings, bushings, and other critical components preventing premature transmission failure
- Protects against corrosion, rust, and foaming

APPLICATIONS:

Torco HiVis & LoVis ATF is suitable for use in high-performance driving, racing, and most OEM automatic transmissions. (Not recommended wherever CVT Fluids or Type F or Power Steering Fluids for Honda are specified).

MEETS/EXCEEDS:

HiVis: Allison C4 • BMW LT 71141; LA 2634; ETL 7045E;8072B • Caterpillar CAT TO-2 • Chrysler ATF +3 • Honda ATF DW-1, Z-1 • GM Dexron-III (H) • Ford Mercon, Mercon V • Hyundai / Kia / Mitsubishi SP-II, SP-III • Jaguar • Land Rover Texaco N402 • Nissan Matic D, Matic J & Matic K • Subaru ATF, ATFHP • Toyota Type WS, T-III, T-IV, JWS 3309 • ZF TE-ML 03D / 04D / 14A / 14B / 17C • VW / Audi Part # G055 025,G 052 165 • JASO 1A-02, JASO 2A-02

LoVis: BMW LT 71141; LA 2634; ETL 7045E;8072B • Honda ATF DW-1, Z-1 • GM Dexron-II, DexronIII (G,H), Dexron-VI • Ford Mercon LV • Hyundai / Kia / Mitsubishi SP-II, SP-III, Diaqueen ATF J-3 • Jaguar • Land Rover Texaco N402 • Nissan Matic D, Matic J & Matic K, Matic S • Subaru ATF, ATF-HP • Toyota, Lexus, Sion Type WS, T-III, T-IV, JWS 3309 • ZF TE-ML 03D / 04D / 14A / 14B / 17C specs • VW / Audi Part # G055 025,G 052 165 • JASO 1A-02, JASO 2A-02

TYPICAL TEST DATA:

TEST	METHOD	LoVis	HiVis
Specific Gravity @ 15.6 °C	D-1298	0.8452	0.8451
Lbs/Gal	D-1298	7.046	7.045
Viscosity @ 100 °C (cSt)	D-445	5.9	7.2
Viscosity Index	D-2270	170	170
Pour Point °C	D-97	-46	-42
Flash Point °C	D-92	218	218