



Technical Data

PRODUCT TECH

©2019 TORCO

V-SERIES TRANS LUBE

SAE 75W-90

>>Description

V-Series Trans Lube is a selective blend of synthetic and petroleum based oils designed to protect all gear face surfaces and bearing components found in Harley® and aftermarket transmissions. Torco's race proven extreme pressure and anti-friction chemistry promotes the highest degree of protection for extended transmission life. This shear stable formula also provides smooth shifting and prevents the formation of rust and oxidation, which is critical during storage.

>>Features

- >Synthetic blend technology
- >Excellent shock load protection
- >Provides smooth, positive shifting
- >Superior anti-rust and oxidation protection
- >Reduces operating temperatures
- >Excellent anti-foam, anti-rust, and anti-oxidation

>>Application

Recommended for use in FL, FLT, FX and FXR transmissions or aftermarket applications that require this specification.

Exceeds manufacturer warranty requirements. Exceeds API GL-5.

>>Typical/Test Data

SAE Grade	ASTM#	75W-90
Appearance	Visual	CL/Amber
API Gravity	D-287	28.4
Lbs/Gal	Tables	7.368
Specific Gravity @ 15.6/15.6°C	D-1298	0.8849
Viscosity @ 100°C	D-445	18.7
Viscosity @ 40°C	D-445	112.18
Viscosity Index	D-2270	187
Pour Point, °C	D-97	-40
Flash Point, °C	D-92	210
Fire Point, °C	D-92	225
Brookfield Viscosity, cP @ °C	D-2983	Pass
Copper Corrosion	D-130	1A

>>Directions

Follow manufacturer fill level requirements. Compatible with other petroleum and synthetic lubricants.

>>Package Sizes / P/N

SAE Grade	75W-90
1-Liter (1.056 US QT)	T737590CE
12/1-Liter Case	T737590C

